



# DUV Raman/PL 200

Fully Integrated,  
Lab Model  
Deep UV Resonance Raman &  
Photoluminescence  
Spectrometer,  
with microscopic imaging

## Features

### Why Deep UV Spectroscopy?

Deep UV excited Raman & photoluminescence spectroscopy is an emerging analytical instrument technology with vast potential for a wide range of commercial, industrial, and research applications. A major limitation of Raman spectroscopy conducted in the near UV, visible, or near IR is obscuration or interference of the Raman signals due to background fluorescence from the analyte or its background or surroundings within the laser beam interrogation spot. This interference limits the types of materials and compositions or backgrounds for which Raman spectroscopy is useful.

Autofluorescence is a phenomenon which does not occur below about 270 nm for the vast majority of materials, independent of excitation wavelength. Raman, on the other hand, is dependent on excitation wavelength and when excitation occurs below 250 nm, there exists a spectral region within which to observe over 3000  $\text{cm}^{-1}$  of Raman shifted emissions without obscuration or interference from fluorescence.

This is the driving motivation for spectroscopy conducted in the deep UV with excitation below 250 nm. Also, operation in the deep UV enables simultaneous detection of Raman and fluorescence spectra, enabling the much higher sensitivity of fluorescence and the higher specificity of Raman spectra. There are many other advantages of operation in the deep UV including enhanced Raman signal strength due to resonance effects, simplification of Raman spectra for resonant materials making spectra easier to interpret, small depth of penetration into many materials, which limits interference with background or substrate materials, and other benefits.

Deep UV resonance Raman & photoluminescence spectroscopy has been hampered by the lack of a suitable laser source in the deep UV. Photon Systems has developed a new enabling laser technology to address this problem. These lasers have exceptionally narrow and stable emission linewidths and are hundreds of times smaller, lighter, and lower power consumption than other deep UV lasers. Photon Systems lasers have been vetted in a wide range of harsh commercial, industrial, and research and have been selected by NASA for the Mars 2020 lander mission for a rover arm mounted deep UV Raman and fluorescence instrument.

**Excitation Wavelength:** 248.6nm.

**Polarization:** Random (Raman signatures insensitive to polarization of target materials)

**Spectrograph:** 200 mm Czerny Turner with dual computer controlled 4200 & 600 g/mm holographic gratings

**Dispersion:** 1.9  $\text{cm}^{-1}$ /pixel (w 4200g/mm grating)

**Resolution:**  $<8 \text{ cm}^{-1}$  with 75  $\mu\text{m}$  slit

**Entrance Slits:** fixed, selectable

**Spectral Spread:** 300-4000  $\text{cm}^{-1}$  (4200g/mm grating) 250nm to 450 nm (600g/mm grating) (0.6 nm res)

**Detector:** 3 stage TE Cooled (-35C), back thinned, back illuminated UV CCD Array. 2048x128 elements, 12x12 micron pixels

**Obj. Lens:** 5X deep UV achromatic objective standard. 3X, 10X, 20X, & 40X objectives available

**Context Imaging Camera:** 2.4 M pixel

**Image FOV:** 1.3mm or less, depending on objective

**Sample Stage:** 50x50x10mm X-Y-Z manual, std.

**Motorized Position/Mapping Stage:** 50x50 mm X-Y motorized, 10mm Z manual, 2 $\mu\text{m}$  resolution, optional as shown

**Size & Weight:** 7.0" W x 8.0" H x 24" D, < 25 lb

**Power Consumption:**

Standby 8 W Max power 60 W

**Input:** 85 VAC to 270 VAC or 24 VDC

**Safety:** Class I, DHHS/CDRH, CE, RoHS

**Command & Control:** External laptop or tablet computer via USB for command, control, data processing, chemometrics, data storage, etc.

**Patents:** U.S. Patents 6,278,869, 7,800,753, 8,395,770, plus pending.



1512 Industrial Park St., Covina, CA 91722 T: 626 967-6431 F: 626 967-5813

www.photonsystems.com

**PNEUM Co., Ltd.**

5-15-3 Minamikoshigaya, Koshigaya-shi,  
Saitama-ken, 343-0845, Japan

TEL: 81-48-985-2720

FAX: 81-48-985-2721  
info@pneum.co.jp 1812