



## The **tunable** laser light source



- CW tunable laser light source
- 450 - 650 nm & 900 - 1300 nm
- Single frequency, < 1 MHz linewidth
- Output power > 200 mW VIS or > 400 mW NIR

### Flexibility with precision

C-WAVE is the first fully-automated tunable laser light source for continuous-wave (CW) emission in the visible and near-infrared wavelength range based on optical parametric oscillation (OPO) technology. Thus, C-WAVE provides tunable high-performance laser light output tuning from blue to red and into the near-infrared by the click of a button. It offers you single frequency operation, narrow spectral linewidth combined with its unprecedented spectral coverage and ease of use to let you focus on your research, not on laser handling.

### Applications:

- Atomic physics
- Quantum optics
- Metrology
- Spectroscopy
- Biophotonics
- Photochemistry
- Holography
- Interferometry

**HÜBNER Photonics** | Coherence matters.


[www.hubner-photonics.com](http://www.hubner-photonics.com) • [photonics@hubner-germany.com](mailto:photonics@hubner-germany.com) • [www.cobolt.se](http://www.cobolt.se) • [info@cobolt.se](mailto:info@cobolt.se)





## Spectral coverage

The concept of C-WAVE allows for building tunable continuous-wave laser light sources from the near UV to the infrared. The bright windows in the spectral coverage chart indicate the full standard tuning range of C-WAVE. Other wavelength ranges are available on request.



## Output power

### Tailored to your needs

Depending on the required output power level, C-WAVE is either pumped by an external single-frequency laser or comes with an integrated laser, making operation and application even easier for you.

### Pump laser options

- Integrated pump laser (1.5 W) – low power
- External pump laser (5 W) – high power


### Tunable output power

#### Low power


- > 200 mW for IR
- > 80 mW for Blue & Orange

#### High power

- > 400 mW for IR
- > 200 mW for Blue & Orange



Typical output power over the visible wavelength range with 5 W pump laser (high power) and 1.5 W pump laser (low power).



Power stability of C-WAVE: Output power over time measured at 571 nm.

Specifications

	VIS <sup>a)</sup>	IR <sup>b)</sup>
Wavelength range	450 - 650 nm <sup>a)</sup> ± 1 nm	900 - 1300 nm <sup>b)</sup> ± 2 nm
Wavelength selection	computer controlled	
Accuracy of wavelength setting		
■ internal	± 1 nm	± 2 nm
■ with external wave-length measurement	< 1 MHz <sup>c)</sup>	< 1 MHz <sup>c)</sup>
Output power		
■ with 1.5 W Low power	> 80 mW	> 200 mW
■ with 5 W High power	> 200 mW	> 400 mW
Amplitude noise	< 5 % <sup>c)</sup>	< 1 % <sup>c)</sup>
Beam polarization	> 1000:1 (horizontal)	
Beam profile	TEM <sub>00</sub> , M <sup>2</sup> < 1.2 <sup>d)</sup>	
Beam radius (1/e <sup>2</sup> )	0.5 mm <sup>c)</sup>	0.2 mm <sup>c)</sup>
Beam divergence (f.a.)	0.5 mrad <sup>c)</sup>	2 mrad <sup>c)</sup>
Linewidth	< 1 MHz (typ. < 500 kHz)	
Mode-hop-free tuning	> 25 GHz <sup>e)</sup>	> 12 GHz <sup>e)</sup>
Warranty	12 months	

<sup>a)</sup> not specified at 525 - 540 (±2) nm; range depending on selected wavelength modules  
<sup>b)</sup> not specified at 1050 - 1080 (±4) nm; range depending on selected wavelength modules  
<sup>c)</sup> typical value  
<sup>d)</sup> not specified at 450 - 480 nm and 900 - 960 nm  
<sup>e)</sup> depending on the pump laser

Requirements

Operating temperature range	20 - 25 °C, constant
Relative humidity	10 - 85 %, non condensing
Mounting surface	vibration-isolated optical table
Environment	free of dust

Technical data

Computer interface	Ethernet / RJ 45
Power supply	110 V / 230 V
Power consumption	< 200 W
Cooling	Closed-loop chiller

Configurations

Wavelength options (multiple selection possible):


- ✓ IR (900 – 1300 nm)\* \* gap at 1050 – 1080 nm
- Blue (450 – 525 nm)
- Orange (540 – 650 nm)

Power options:

- Low power:
  - > 200 mW for IR
  - > 80 mW for Blue & Orange
- High power:
  - > 400 mW for IR
  - > 200 mW for Blue & Orange

Add-ons

- Fiber coupling VIS & IR
- Low noise add-on: Noise Eater setup
- Frequency stabilization on external reference: AbsoluteLambda™




Dimensions

Length	575 mm
Width	410 mm
Height	155 mm
Weight	34 kg



Designed according to UL standards.





## Headquarters

**HÜBNER Photonics**  
**(Sales in Germany, Switzerland and Austria)**  
 HÜBNER GmbH & Co. KG  
 Heinrich-Hertz Strasse 2,  
 34123 Kassel, Germany

Phone: +49 561 998 0  
 Fax: +49 561 998 1515  
 E-mail: [photonics@hubner-germany.com](mailto:photonics@hubner-germany.com)

[www.hubner-photonics.com](http://www.hubner-photonics.com)

**Cobolt AB**  
**(Sales in Norway, Sweden, Finland and Denmark)**  
 Vretenvägen 13,  
 SE-171 54 Solna, Sweden

Phone: +46 8 545 912 30  
 Fax: +46 8 545 912 31  
 E-mail: [info@coboltlasers.com](mailto:info@coboltlasers.com)

[www.coboltlasers.com](http://www.coboltlasers.com)

## Direct sales offices

**HUBNER Photonics Inc**  
**(Sales in USA, Canada & Mexico)**  
 2635 North First Street, Suite 228,  
 San José, California, 95134, USA

Phone: +1(408)708 4351  
 Fax: +1(408)490 2774  
 E-mail: [info.usa@hubner-photonics.com](mailto:info.usa@hubner-photonics.com)

**HÜBNER Photonics UK**  
**(Sales in UK & Ireland)**  
 Royal Mail House, Terminus Terrace,  
 Southampton, Hampshire, SO14 3FD

Phone: +44 2380 438701  
 E-mail: [info.uk@hubner-photonics.com](mailto:info.uk@hubner-photonics.com)

### **PNEUM Co., Ltd.**

5-15-3 Minamikoshigaya, Koshigaya-shi,  
 Saitama-ken, 343-0845, Japan

TEL: 81-48-985-2720  
 FAX: 81-48-985-2721  
[info@pneum.co.jp](mailto:info@pneum.co.jp) **1903**

