

# FASTLITE

Ultrafast - Shaping - Measurement - Control



## DAZZLER™ WB45-2000-3700

Wide Band-cut 45mm DAZZLER™

### Specifications

PROGRAMMABLE AMPLITUDE AND PHASE FILTER  
FOR FEMTOSECOND LASER PULSE SHAPING

- ✓ Ultra-compact device
- ✓ In-line geometry
- ✓ Advanced software functionalities
- ✓ Simple optical alignment

• Wavelength tuning range	2000 nm to 3700 nm
○ Wavelengths outside this range are poorly or not diffracted	
• Instantaneous bandwidth	up to 1700 nm
• Spectral resolution	3.5 nm at 2500 nm 7 nm at 3500 nm
• Intensity control dynamic range	> 45 dB
• Maximum programmable delay	5.5 ps at 2800 nm
• Diffraction efficiency for operation up to 7.5 kHz	50% on a 200 nm bandwidth 25% on a 400 nm bandwidth 35% on a 400 nm bandwidth 50% on a 600 nm bandwidth
○ With optional 20W RF amplifier (up to 4.5kHz)	
○ With optional 50W external RF amplifier (up to 2kHz)	
• Typical acoustic waveform refreshing time	< 3ms
• Input beam requirements	30 μJ max on $\phi = 2.5$ mm, collimated
• Optical module dimensions	48 x 98 x 22 mm <sup>3</sup>
• Typical optical jitter	< 10 fs < 100 as
○ With optional Low-jitter electronics	

### ✓ Special feature for CEP control

Multi-kHz rate CEP control with the optional CEP modulation solution. This additional hardware allows dispersion-free, single-shot control of the CEP value down to 6mrad resolution.



Phone: +33 (0)4 88 13 17 51

Fax: +33 (0)4 92 95 76 90

E-mail: [info@fastlite.com](mailto:info@fastlite.com)

**FASTLITE**

[www.fastlite.com](http://www.fastlite.com)

Les collines de Sophia, Bât D1

1900 route des crêtes 06560

VALBONNE, FRANCE

**PNEUM Co., Ltd.**

5-15-3 Minamikoshigaya, Koshigaya-shi,  
Saitama-ken, 343-0845, Japan

TEL: 81-48-985-2720

FAX: 81-48-985-2721

[info@pneum.co.jp](mailto:info@pneum.co.jp) 1607

Spec-WB45-2000-3700-rev2016-1 9/3/2016