

WIZZLER

Femtosecond pulse measurement device

Standard Models



- Highest dynamic range
- Single shot, single beam
- Extreme ease of use
- Calibration-free
- Direct retrieval algorithm
- Data logging
- Pulse compression optimization for Dazzler users

Wizzler products are based on a unique technique invented and patented by FASTLITE, in which a reference pulse with a flat spectral phase is collinearly generated from the input pulse by cross-polarized wave generation (XPW). The spectral interference pattern resulting from the combination of the input pulse and the reference pulse allows direct retrieval of the spectral phase and intensity.

Publications:

T.Oksenhendler et al: "Self-referenced spectral interferometry"
Appl. Phys.B (2010)

A.Moulet et al: "Single-shot, high dynamic-range measurement of sub-15fs pulses by self-referenced spectral interferometry"
Opt.Lett. (2010)

S.Gabielle et al: "Self-referenced spectral interferometry cross-checked with SPIDER on sub-15 fs pulses."
Nima. (2011)

A.Trabattoni et al: "Self-referenced spectral interferometry for single-shot measurement of sub-5fs pulses"
RSI (2015)

Phone: +33 (0)4 88 13 17 51
Fax: +33 (0)4 92 95 76 90
E-mail: info@fastlite.com

FASTLITE
www.fastlite.com

Pole euro 95 - Bat D
165 rue des Cistes
06600 Antibes, FRANCE

FASTLITE

Ultrafast - Shaping - Measurement - Control

WIZZLER

Specifications

	Wizzler 400	Wizzler USP8	Wizzler USP4	Wizzler 800	Wizzler 1030
Spectral detection band edges	380-400 nm	550-1050 nm	360-1100 nm	550-1050 nm	930-1100 nm
Pulse duration range	35 - 100 fs(*)	8 - 100 fs(*)	4 - 100 fs(**)	20 - 100 fs(*)	50 - 1000 fs(*)
Temporal measurement window	±400 fs	±400 fs	±380 fs	±400 fs	±2500 fs ±800 fs for pulses <100fs
Temporal measurement dynamic	>40 dB	>40 dB	>40 dB	>40 dB	>40 dB
Required pulse energy	2-20 μJ	5-15 μJ	5-15 μJ	2-20 μJ	2-20 μJ


(*) FWHM values for FTL Gaussian pulses
 (**) For typical few-cycle spectrum shapes

For other pulse durations or other wavelengths, please contact us

Additional feature for Dazzler users:

High dynamic pulse compression using the included Dazzler / Wizzler feedback loop

- Increase contrast and peak power
- Day-to-day FTL pulses
- Day-to-day reproducible results



Wizzler measurements of a Ti:Sa amplifier (1kHz, 1mJ, 25fs FWHM) before and after the Dazzler / Wizzler feedback loop.

Requirements

Input pulse :

- Polarization linear
- Min/Max energy see specification table
- Max average power 1 W
- Beam diameter 3mm, collimated
- Pulse compression < 2 x FTL pulse duration
- Beam Height adjustable down to 35mm

PC: Windows 10, with 2 USB ports

Dimensions: 257x109mm

